

MULTI SPEED FLOOR FINISH

RENO2823-MS
(107458)
RENO2824-MS
(107459)
RENO2923-MS
(100989)

Features:

- Smooth Leveling
- Excellent Adhesion
- Non-Yellowing

Description:

This floor finish is highly versatile and easy to use. Built as a tough scuff resistant high solids floor finish, it resists wear between maintenance procedures. This product is ideal for all surfaces and all speed maintenance programs. Requires no special application techniques. Provides smooth leveling, excellent adhesion, and non-yellowing characteristics. Dries to a brilliant gloss without buffing.

Directions:

Use: PREPARATION: If stripping is necessary, use a high quality stripper and follow directions accordingly. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow drying completely.

FINISHING: Apply 2 or 3 liberal coats of finish using a clean mop. Allow a minimum of 45 minutes drying time between coats. Apply additional coats to obtain desired gloss.

BURNISHING: Dust mop or sweep thoroughly. Clean floor with a neutral floor cleaner diluted according to directions. Burnish using the appropriate pads.

RESTORATION: Dust mop or sweep thoroughly. Dilute restorer according to manufacturer direction and apply to floor with clean mop or auto-scrubber. Allow to dry to a haze and buff out with any type of UHS equipment: propane, battery, or cord electric.

RECOATING: Dust mop or sweep thoroughly. Deep scrub using a neutral floor cleaner diluted according to directions. Apply 1 or 2 liberal coats of finish using a clean mop.

TECHNICAL INFORMATION:	
Non-volatile Solids:	20.0±0.5%
Color:	Milky emulsion
Odor:	Mild
pH:	8.0 - 9.0
Dry/Recoat Time:	45 minutes min.
Slip Resistance:	0.5 min. by (ASTM-D2047)
Leveling:	Excellent
Buffability:	Dry burnish/Spray buff
Removability:	With instant type strippers
Coverage:	Up to 2000-2500
	sq. ft. per gal.
Detergent Resistance:	Excellent
Heel Mark Resistance:	Excellent
VOC Content:	0.40 lbs./gal.
Storage/Stability:	2 years
Weight per Gallon:	8.62 lbs./gal.
Freeze/Thaw Stability:	Keep from freezing

