

UHS FLOOR FINISH

RENO2826-MS
(107461)
RENO2827-MS
(107462)
RENO2929-MS
(100992)

Features:

- Excellent Response to Burnishing
- No Sealer Required
- Excellent Durability

Description:

This floor finish is specially designed for use with ultra high speed buffing equipment, insuring excellent results and achieving outstanding savings with your ultra high speed system. UHS Floor Finish has the following features: initial “wet look” gloss, impressive burnish response, excellent durability, scuff, and black mark resistance.

Directions:

Use: **PREPARATION:** If stripping is necessary, use a high quality stripper and follow directions accordingly. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow drying completely.

FINISHING: Apply 1 or 2 coats of floor sealer if desired. Apply 4 liberal coats of finish using a clean mop. Allow a minimum of 30 minutes drying time between coats. Apply additional coats to obtain desired gloss.

BURNISHING: Dust mop or sweep thoroughly. Clean floor with a neutral floor cleaner diluted according to directions. Burnish using the appropriate pads.

RESTORATION: Dust mop or sweep thoroughly. Dilute restorer according to directions and apply to floor with clean mop or auto-scrubber. Allow to dry to a haze and buff out with any type of UHS equipment: propane, battery, or cord electric burnisher.

RECOATING: Dust mop or sweep thoroughly. Deep scrub using a neutral floor cleaner diluted according to directions. Apply 1 or 2 liberal coats of finish using a clean mop.

TECHNICAL INFORMATION:

Non-volatile Solids:	20.0 + 0.5%
Color:	Milky emulsion
Odor:	Mild
pH:	8.0 – 9.0
Dry/Recoat Time:	30 minutes min.
Slip Resistance:	0.5 min. by ASTM-D2047
Leveling:	Excellent
Buffability:	Excellent
Removability:	With instant type strippers
Detergent Resistance:	Excellent
Heel Mark Resistance:	Excellent
VOC Content:	0.44 lbs./gal.
Storage/Stability:	2 years
Weight per Gallon:	8.60 lbs./gal.
Freeze/Thaw Stability:	Keep from freezing
Weight per Gallon:	8.45 lbs. per gallon
Coverage:	1,800 - 2,200 sq. ft./ gal

