

UNDER COAT SEALER

RENO2830-MS
(107463)
RENO2924-MS
RENO2925-MS

Features:

- Fast Drying
- Non-Yellowing
- Excellent Durability

Description:

An all-acrylic floor sealer formulated to provide a hard, durable undercoat for use prior to the application of any floor finish. Never yellows and will continue to protect your floor after all floor finish or wax has worn off.

Directions:

Use: Make sure floor has been thoroughly stripped and rinsed and allowed to dry. For porous or well-worn floors, apply 2 coats of sealer followed by 2 or more coats of finish depending on the gloss desired. On new floor or floors in good condition, one coat of sealer should suffice.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by State and Federal regulations.

TECHNICAL INFORMATION:	
Type:	Modified acrylic
Non-volatile Solids:	18.0±0.5%
Color:	Milky white
Odor:	Mild
pH:	8.5 - 9.0
Dry/Recoat Time:	30 minutes
Slip Resistance:	0.5 min. by ASTM D2047
Leveling:	Excellent
Sediment:	0.1% by volume, max.
Removability:	With conventional strippers
Detergent Resistance:	Excellent
Stain Resistance:	Good
Chemical Resistance:	Good
VOC Content:	0.31 lbs./gal.
Storage/Stability:	2 years
Freeze/Thaw Stability:	Keep from freezing
Weight per Gallon:	8.56 lbs./gal.
Coverage:	1500-2000 ft ² per gal.

