

**REN02706-MS
(107445)
REN02910-MS
(107472)**

SUPER FINISH II

Features:

- Excellent Gloss
- Can be spray buffed or burnished
- Resists scuffs, abrasions, and black heel marks
- Easy to apply

Description:

This high solid burnishable floor finish is the professional choice for great performance and protection on all types of resilient flooring. The ultimate, easy to apply, high initial gloss, durable floor finish is self sealing for less labor and increased durability.

Directions:

PREPARATION: If stripping is necessary, use a high quality stripper and follow directions accordingly. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow drying completely.

FINISHING: Apply 2 or 3 liberal coats of finish using a clean mop. Allow a minimum of 45 minutes drying time between coats. Apply additional coat to obtain desired gloss.

BURNISHING: Dust mop or sweep thoroughly. Clean floor with a neutral floor cleaner diluted according to directions. Burnish using the appropriate pads.

RESTORATION: Dust mop or sweep thoroughly. Dilute restorer according to manufacturer direction and apply to floor with clean mop or auto-scrubber. Allow to dry to a haze and buff out with any type of UHS equipment: propane, battery, or cord electric.

RECOATING: Dust mop or sweep thoroughly. Deep scrub using a neutral floor cleaner diluted according to directions. Apply 1 or 2 liberal coats of finish using a clean mop.

TECHNICAL INFORMATION:	
Non-volatile Solids:	25.0±0.5%
Color:	Milky white
Odor:	Mild
pH:	8.0 - 9.0
Dry/Recoat Time:	45 minutes min.
Slip Resistance:	0.5 min. by ASTM D2047
Leveling:	Excellent
Buffability:	Dry burnish / spray buff
Coverage:	Up to 2000-2500 sq.ft. per gal.
Removability:	With instant type strippers
Detergent Resistance:	Excellent
Heel Mark Resistance:	Excellent
VOC Content:	0.48 lbs./gal.
Storage/Stability:	1 year
Freeze/Thaw Stability:	Keep from freezing
Weight per Gallon:	8.66 lbs./gal.

