

Lights Up^{TM/MC}

High Solids Floor Finish

REN02911
(297214)

REN02912
(297215)

Features:

- Applies easily and levels perfectly with no mop drag
- Great mark resistance and durability
- Install up to five coats in one night
- Low odor finish is ideal for 24-hour facilities

Description:

High solids durable finish. Superior initial gloss. Builds gloss with fewer coats than other finishes. Applies easily and levels perfectly with no mop drag. Great mark resistance and durability. Excellent response to spray buffing or UHS burnishing. For use on Asphalt Tile, Marble, Stone, Terrazzo, Tile, Vinyl.

Directions:

PREPARATION: Always barricade area to be finished. Before the first application of Lights Up High Solids Finish, remove all old finish with recommended stripper.

COATING: Apply 3 or more medium coats of Lights Up High Solids Finish with a clean finish mop. Let dry to the touch between coats (about 30 minutes). On porous resilient or stone floors, seal first with 2 coats of recommended sealer.

MAINTENANCE: Clean Daily: Dust mop. Then wet clean with recommended cleaner in an autoscrubber or with a damp mop. Spray buff as needed with recommended spray buff, a red or beige pad and a 175–1500 RPM machine. Or burnish with a UHS pad and a battery, cord electric or propane machine at 1500–2000+ RPM. Clean and restore gloss with recommended cleaner/maintainer. Apply recommended cleaner/maintainer using an autoscrubber or damp mop, let floor dry and then burnish.

RECOAT: Clean thoroughly. Dust mop. Machine scrub with a floor machine or autoscrubber using a blue pad and the recommended cleaner at the recommended dilution. Rinse well and let dry. Apply 2 new coats of Lights Up High Solids Floor Finish.

Technical Information	
Solids Content:	25%
Color/Odor:	Opaque White/Bland
pH:	7.9 - 8.5
Dilution:	RTU
Dry/Recoat Time:	30 Minutes
Slip Resistance:	0.5 minimum (ASTM D2047)
Coverage:	2000-2500 sq ft per gal.
Leveling:	Excellent
Buffability:	Dry burnish / spray buff
Removability:	Conventional Stripper
Detergent Resistance	Excellent
Heel Mark Resistance	Excellent
VOC Content:	0.95%
Flash Point:	> 200° F (> 93.4° C)
Solubility:	Completely Soluble
Shelf Life:	2 Years
Freeze/Thaw Stability:	Keep from freezing
Weight per Gallon:	8.59 lbs/gal 1.03 Kg/L

